

INDUSTRIAL SIRENS

ACOUSTIC

AS300M



AS400M





Acoustic Signals Industrial Sirens > AS300M & AS400M Series

Product overview



These sirens have been designed for a wide range of applications where a loud commanding signal is required. The AS300 Series is designed for surface mounting with a separate mounting plate to allow for ease of installation.

The unit comes pre-wired and is supplied with 1 metre of cable. The AS400M Series is a vertical mounted siren, manufactured for heavy duty environments and is of rugged construction. The low frequency it produces is ideal for use over medium size areas. Both sirens are weatherproof when mounted according to instructions supplied.

AS300



AS400



Features

Continuously rated

High sound output

AS300M - 127 dB

AS400M - 125 dB for Ac

AS400M - 116 dB for Dc at 1 m

IP55 - AS300M


IP65 - AS400M

Material

AS300M - ABS Construction

AS400M - Cast Aluminium Body and Noryl Rotor

Code No:	Voltage:	Frequency:	Current:
AS300M-115	115v Ac/Dc \approx	1680 Hz	2.7A
AS300M-230	230v Ac/Dc \approx	1680 Hz	1.0A
AS400M-24 •	24v Dc ---	900 Hz	8.0A
AS400M-115 •	115v Ac/Dc \approx	900 Hz	3.0A
AS400M-230 •	230v Ac/Dc \approx	900 Hz	1.4A



Kg 1.8kg AS300M
4.5kg AS400M

50/60 Hz

°C -30+45

IP 55/65 •

ANCHOR MARINE

INDUSTRIAL

APPROVED AND CONFORMITIES



FIRE