

High Output
Version



ECO
Version

Audible Signals - Industrial ECO TLM AUDIBLE MODULES

Industrial LED-TLM ECO Tower Light > Audible Modules

Product overview

These audible modules have been designed for use in conjunction with the Moflash LED-TLM ECO Tower Light Module range. They are a simple addition that offer an audible warning signal in addition to the multiple visual ones the tower offers.

The two ECO modules (LED-TLM-AUD-02 & LED-TLM-AUD-04)

incorporate two sound outputs, continuous or pulsed, which are selectable via a switch located on the PCB. The volume can also be controlled via a small pot also located on the PCB. These sounders have been designed for local indication only.

A higher decibel output version is also available (LED-TLM-AUD120-04) allowing for up to 120dB. The sound output and volume are controlled via independent pots located on the PCB.

Features



- Continuously rated
- Low current consumption
- Cost effective audible solution
- Quick & easy installation or upgrade

Material

Black ABS Plastic



ECO TLM-AUD-02 >

Code No:	LED-TLM-AUD-02
Voltage:	24v Dc ---
Operating Temperature:	-25 to +55 °C
Current:	55mA
Tone Frequency:	1300-1500 Hz
Pulsed Tone Rate:	60/80 (time/min)
Output dB:	100
IP Protection:	IP65






ECO TLM-AUD-04 >

Code No:	LED-TLM-AUD-04
Voltage:	85-275v Ac ~
Operating Temperature:	-25 to +55 °C
Current:	<55mA
Tone Frequency:	1300-1500 Hz
Output dB:	80
IP Protection:	IP65



HIGH OUTPUT TLM-AUD120-04 >

Code No:	LED-TLM-AUD120-04
Voltage:	85-275v Ac ~
Operating Temperature:	-25 to +55 °C
Current:	<20mA
Tone Frequency:	1500-7500Hz
Output dB:	100-120 selectable
IP Protection:	IP65



APPROVALS and
CONFORMITIES

